

WARN[®] ZEON[™] 10 Winch Truck/SUV winch equipped with steel rope and a 10,000 lb. capacity.


The next generation of winches is here: WARN[®] ZEON.[™] With a modern rugged design, upgraded internal components, and increased performance and durability, ZEON is a new name from the most trusted name in winches. With a bold look and power to match, the ZEON is like nothing you've ever seen before.

- Legendary WARN reliability and performance; 10,000 lb. (4536 kg) capacity – perfect for heavier trucks and SUVs
- Includes 80' of 3/8" steel rope
- Unique exterior styling and symmetrical design give this winch a look that is advanced, capable, and strong
- New-design planetary geartrain and series-wound motor deliver fast, quiet, and reliable pulling power
- Satin-black powder-coated finish with stainless steel fasteners and clutch lever looks great and inhibits corrosion
- Convertible control pack can be attached to the winch or remotely mounted, allowing for various winch mounting options and looks (Relocation kit required and sold separately)

- Large diameter, aluminum winch drum reduces rope wear, is light weight, and has an integrated rope anchor for easy rope installation
- Robust aluminum housing is durable and helps dissipate heat
- Improved winch sealing to keep the elements out; IP68 rated
- · Contactor control for extreme reliability and weather resistance
- Automatic mechanical cone brake holds the full-rated load and offers excellent control while winching
- Ultra-durable rubberized corded remote with 12' lead

PN 89650 (CE, for International sales only)





SPECIFICATIONS

Winch model: WARN ZEON 10

Part numbers: 89650 (CE, for InternationI sales only)

Rated line pull: 10,000 lbs. (4536 kg) single-line

Motor: 12V DC, series wound

Electrical controls: Contactor

Remote Control: Remote switch, 12' (3.7m) lead

Geartrain: 3-stage planetary

Gear ratio: 216:1

Clutch (freespooling): Rotating ring gear

Brake: Automatic mechanical cone

Drum diameter/Length: 3.15"/9.0" (80mm/229mm)

Weight (kit shipping): 98 lbs. (44 kg)

Rope: 3/8" x 80' (9.52mm x 24.38m) steel

Fairlead: Roller


Recommended Battery: 650 CCA minimum for winching

Battery leads: 2 gauge, 72" (1.83m)

Finish: Satin-black powder coat

12V DC performance specs (first layer of drum)

Line Pull	Line Speed	Motor
Lbs. (Kg)	Ft./min. (M/min.)	Current
0	33.7 (10.3)	62 amps
2000 (910)	14.9 (4.5)	144 amps
4000 (1810)	11.2 (3.4)	215 amps
6000 (2720)	8.5 (2.6)	280 amps
8000 (3630)	6.5 (1.9)	343 amps
10000 (4536)	4.8 (1.5)	409 amps



Winch dimensions:

Integrated configuration: 24.25" L x 7.15" D x 10.52" H (615.9mm L x 181.6mm D x 267.1mm H) Low-profile configuration: 24.25" L x 7.15" D x 7.84" H (615.9mm L x 181.6mm D x 199.02mm H)

Mounting bolt pattern:

10.0" x 4.5" (254mm x 114.3mm)

Warn Industries, Inc. 12900 S.E. Capps Road, Clackamas, OR USA 97015-8903



International Sales Support: +1 503 722 1200

www.warn.com