

R580 Transparent



Features

- Diameter 580mm
- Modern, stylish and Innovative design
- Uniform light output
- Up/Down Lighting Optional
- Transparent Optional
- White/Black/Silver finishing available
- Durable with life span over 50,000 hours
- 5 Years Guarantee
- Simple and convenient installation

Applications

Meets the general and decoration lighting environment such as:

- Offices
- Restaurants
- Hotels
- Shops
- Schools and Hospitals
- Hallway & lobbies
- Meeting Rooms



REV 1.1

08/26/2016

Sheenly LED Round Panel Light



Sheenly LED Round Panel Light adopts qualified super bright LED as light source, which is stable, long life and no UV & IR emission. The anodized aluminum frame is stylish and fashionable with everlasting color. It is powered by low voltage constant current driver, which is safety, energy saving and long life.

Sheenly LED Panel light is the ideal replacement for traditional grid lights and fluorescent tubes. Moreover, Sheenly Panel light creates extremely harmonies and uniform lights, which conventional light never achieved.

Specifications

Dimension	D580*15 mm
Power & Lumen Output	
40W	3400 lm @ 4000K
60W	5000 lm @ 4000K
Color Temperature	
Warm White	3000 ±200K
Natural White	4000 ±250K
Pure White	5700 ±350K
Color Rendering Index	>80
Rated Life (L70)	50,000 Hours
Housing	Aluminum
Optics	Opal
Beam Spread	120°
Operating Temperature	-20°C to +45°C (Amb.)
Input Voltage	200-240V/AC
Power Factor	>0.95
Working Voltage	
40W	25 V/DC
60W	38 V/DC
Working Current	
	40W@1050mA
	60W@1400mA
Net Weight	3.15 Kg
Glow Wire	650 °C (850°C Optional)
IP	IP40
IK	IK05
Installation	Suspension
	Surface Mounted

Dimension and Illumination Diagram



Ordering Information

Sheenly	Class	Watt	CCT	Model	Finishing	Options
SL=Sheenly Lighting	PAN=Panel	40W 60W	WW=3000 ±200K NW=4000 ±250K PW=5700 ±350K	R60	BK=Black WH=White	UD=Up/down Lighting TP=Transparent

*Standard finishing comes in White, for other finishing color please specify when place the order.

Part Number	Power	CCT	Lumen Output	Beam	Dimension
SL-PAN-40W-WW-R60-UD-TP	40W	3000K/4000K/5700K	3400	120°	D580*15 mm
SL-PAN-40W-NW-R60-UD-TP			3400	120°	D580*15 mm
SL-PAN-40W-PW-R60-UD-TP			3400	120°	D580*15 mm
SL-PAN-60W-WW-R60-UD-TP	60W	3000K/4000K/5700K	5000	120°	D580*15 mm
SL-PAN-60W-NW-R60-UD-TP			5000	120°	D580*15 mm
SL-PAN-60W-PW-R60-UD-TP			5000	120°	D580*15 mm

Accessory



Suspension Kit:
Round Driver Box, Steel Cables, Screws, etc.



Shanghai Sheenly Lighting Co., Ltd.

No. 2755 SanLu Road, Minhang District Shanghai 201112, China

Tel: (+86)-21-6411 3138 Fax: (+86)-21-6411 3862

*All specifications subject to change without notice.

©2009-2016 Sheenly Lighting all rights reserved.

LED Round Panel Light R580 - Suspension



Step 1

Dimension	A(mm)
D580	120

Step 2

Step 3

L Brown
 ⊕ Yellow
 N Blue

Step 4

Step 5

Step 6

Step 7

X2 X2 X2 X3 X3 X3

**Lighting Up
a New World**