



DoorBird Video Door Station D101, Polycarbonate housing, White Edition



D101 with faceplate F101





Technical data

General		Video	
Housing	Polycarbonate, UV-resistant	Camera	HDTV 720p, dynamic (VGA – HDTV)
Doorbell button	Stainless-steel button with illuminated LED Ring	Lens	High-end Ultra wide-angle Hemispheric Lens 180° horizontal, 90° vertical, straightened, IR-capable
Nameplate	Optional, can be engraved on the faceplate	Night-vision	Yes, Light sensor, Automatic IR-Cut Filter
Mounting type	Surface-mounted	Audio	
Power supply	15VDC (power 110-240VAC) or Power over Ethernet (PoE 802.3af Mode-A)	Audio components	Speaker and microphone, Echo and Noise Canceller
Weight	290g	Audio streaming	Two-way
Connectors	Power, Electric door opener / strike, Door chime, Door opener button, Network	Network	
Outdoor-ready	Yes, IP54	WiFi	802.11b/g/n 2.4GHz
Approvals	CE, IC, FCC, IP54	Ethernet	Connector
Dimensions	157 x 75 x 35mm (H x W x D)	Motion sensor	
Operating conditions	- 20 to +40°C Humidity 10 to 85% RH (non condensing)	Type	Passive Infrared sensor (PIR)
Included accessories	Video Door Station, Mounting plate, Power supply unit (world-wide, 110 - 240V), DIN-Rail power supply sold separately, Screw package, Quickstart Guide	Detection angle	180°
EAN	4260423860001	Range	2-8m (dep. on environm.)
Current system requirements		Illumination	
Mobile device	Latest iOS on iPhone /iPad, latest Android on Smartphone or Tablet	Lighting ring	12 intelligent Infrared LEDs
Internet	High-Speed landline broadband Internet connection, DSL, cable or Fiber, min. 500kbs Uploadbandwidth, no Socks- or Proxyserver	Range	2-8m (dep. on environm.)
Network	802.11b/g/n 2.4GHz or Ethernet network, with DHCP	Integrated wireless modules	
Recommended installation height	Camera lens should be at a min. height of 125cm	WiFi	2,4 GHz, internal antenna
		RFID	433 MHz, internal antenna
		Bluetooth	Available separately
		Optional accessories	
		Sold separately	Faceplate F101, Faceplate F103, DIN-Rail Power supply A002, BirdGuard B101