

PRODUCT INFORMATION



Automotive Chemicals – Technical Spray - Tool

Version: **TS/014**

Valvoline™ Gasket Remover

High quality spray for fast and easy removal of dried adhesives and seals, as well as hardened sealing materials in cars and machine parts.

Applications

Cylinder heads
Gear boxes
Exhausts
Crankcases
Sanitary fittings
Water and oil pumps
Electro engines

Product characteristics

User friendly
High dissolving properties
Optimum effect in view of high viscosity
Non-conductive
Slight gel structure
Non-corrosive
Directed jet spray
360° valve

Directions for use:

Before use, carefully read the directions on the packaging.

Valvoline™ Gasket Remover should be at room temperature before use. The processing temperature should be between 5 to 30°C. Shake before use.

Cover lacquered and plastic parts

Apply Valvoline™ Gasket Remover in an equal layer on the parts to be treated and allow to take effect for approx. 10 minutes.

Carefully remove the dissolved residues with a filling-knife.

With persistent contamination, repeat the treatment.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineeurope.com

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Valvoline™ Gasket Remover	
Contents	500 ml
Basis	Dimethoxymethane
VOC-content	Approximately 95% w/w
Colour	Transparent
Scent	Ether
Relative density @ 20°C	0,75 g/ml
Yield	1,0 – 1,5 g/sec
Vapour pressure @ 20°C	2 to 3 bar
pH-value	Neutral

This information only applies to products manufactured in the following location(s): Europe

™ Trademark of Valvoline, registered in various countries © 2018

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://sds.valvoline.com>

Protect the environment

Take used chemicals to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces –