

PRODUCT INFORMATION



Lubricants - Agricultural

Version: 701/03e

Valvoline™ STOU SAE 10W-40

STOU is a premium multi-functional oil specially formulated for use in agricultural equipment, engines, transmissions, and differentials with wet brake system and integrated hydraulic system. The product can be used for total tractor lubrication and is recommended for many tractor manufacturers.

| Performance levels |
|----------------------------------|
| API: CF-4/SF |
| API: GL-4 |
| Allison C4 |
| Ford M2C134 A, 159 B, 159 C |
| FNH 82009203 |
| John Deere J27 |
| MF M1144, M1145 |
| ZF TE-ML 05K, 06B, 06C, 07B, 07D |

| Suitable for use in**: |
|------------------------|
| AGCO CVT |
| Claas CVT |
| Fendt Vario |

Applications

Total tractor lubrication for the engine, gearbox, differential, hydraulic system.

Suitable for use in implements.
Tractors with wet brake systems
Power take-offs.
Combines.
Earthmoving machines.
Forklifts.

**Available in 10W-30, 10W-40 and 15W-40.*

***Check owner's manual before use*

Features & Benefits

Wear protection

Super Tractor Oil Universal is specially formulated for agricultural use, adjusted to different circumstances like low speed/high torque etc. The carefully chosen base oils and additive system form a protective oil film for all the tractor components.

Tractor component cleanliness

Detergent and dispersant additives keep the engine, gearbox, differential, and hydraulic system clean and in good condition. The oil is resistant against moist and oxidation.

Multi-Purpose

Super Tractor Oil Universal can be used for the engine, the gearbox, the differential, and the hydraulic system. A real multipurpose use, providing one oil for the whole tractor, resulting in less storage and reduced miss-applications.

Break Down resistance

Thermal and oxidation stable oil film.
Special Extreme Pressure additives protect the tractor components against break down.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineeurope.com

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

| STOU | |
|--|--------|
| SAE Viscosity Grade | 10W-40 |
| Viscosity, mm²/s @ 100 °C. ASTM D-445 | 13,1 |
| Viscosity, mm²/s @ 40 °C. ASTM D-445 | 87 |
| Viscosity Index ASTM D-2270 | 150 |
| Viscosity, mPa.s -25°C. ASTM D-5293 | < 7000 |
| TBN, mg KOH/g ASTM D-2896 | 10,5 |
| TAN, mg KOH/g ASTM D-664 | 4,8 |
| Pour Point, °C ASTM D-5949 | -42 |
| Specific Gravity @ 15.6°C. ASTM D-4052 | 0,868 |
| Flash Point, COC, °C. ASTM D-92 | 226 |

**This information only applies to products manufactured in the following location(s):
Europe**

™ Trademark of Valvoline, registered in various countries © 2019

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://sds.valvoline.com>

Protect the environment

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces – 701/03d