

Tyyppi ja tilavuus l	LVI-nro	Teho kW	Jännite V	Paino ilm. vettä	Lämmitys aika 30-65 °C	Varolaite	Putki koko NS	Korkeus mm	Leveys mm	Syvyys mm
2-HK 15	5253010	1/3	230/400	18	n. 1/2	muk toim	15mm	390	390	288
3-HK 35	5253015	2	230	17	n. 3/4	on	15mm	565	467	455
3-HK 55	5253020	2	230	22	m. 1 1/2	on	15mm	750	467	455
3-HK 100	5253022	2	230	31	2	on	15mm	1120	467	455
2-HK 150	5253065	2/3	230/400	58	2 3/4	on	22mm	1140	600	615
2-HK 200	5253070	2/3	230/400	67	3	on	22mm	1330	600	615
2-HK 300	5253075	2/3	230/400	87	4	on	22mm	1850	600	615
2-HM 150	5253045	2/3	230/400	38	2 1/2	on	22mm	701	890	600
2-HM 230	5253050	2/3	230/400	51	3	on	22mm	701	1320	600
2-HM 230r	5253051	2/3	230/400	51	3	on	22mm	701	1320	600
2-HM 300	5253055	2/3	230/400	62	4	on	22mm	701	1610	600