



Fulfill your customers' highest demands on the hygiene of drinking water and efficiency - with the horizontal OEG hygienic storage tanks!

The structure of these storage tanks is fundamentally different from usual large-volume domestic water tanks. A built-in corrugated stainless steel pipe separates the drinking water from the heating water and serves as a powerful heat exchanger at the same time. Thus, the advantages of a buffer tank are combined with those of a flow heater.

The drinking water flows through the corrugated stainless steel pipe in the water of the heated tank only if required. This leads to a very low energy consumption and you can guarantee your customers legionella-free drinking water. You will not need a legionella protection programme in the regulation. At all times, customers are provided with hygienically-clean, fresh water at the desired temperature.

The horizontal arrangement of these hygienic storage tanks is ideal for the use in places that must be ruled out for vertical tanks (e.g. below inclined walls and stairs). Thus, your customers can benefit from the advantages of a hygienic storage tank even if space is limited.

Just compare! By positioning the heat exchangers horizontally in these storage tanks, you provide your customers with advantages over other products on the market. An efficient thermal stratification is only achieved by horizontal installation of the heat exchangers. The generously dimensioned heat exchanger surfaces ensure another energetic advantage over other products available in the market.

Due to the two additional heat exchangers, you offer your customer the option to use more heat generators and to feed their energy into the hygienic storage tank.

## General

OEG Nr.:	516006384
rated volume according to EN 12897:	300
Colour:	silver
Insulation according to DIN 4102-1 Fire Protection Class B2:	firmly foamed A+ insulation
Weight [kg]:	120
Total height including insulation [mm]:	700
Width [cm]:	610
Length [cm]:	1750

## Energy

Energy efficiency class according to EU regulation no. 812/2013:	A+
Heat loss according to EN 12897 [W]:	36
Heat losses in stand-by mode according to DIN 12897 [kW/h / 24 h]:	0,864
Output capacity (45°) [l]:	175

# OEG Horizontal Hygienic Tank 300 litres 2 additional heat exchangers



---

Performance indicator NL following DIN 4708:	1,60
--	------

## Tank

---

Real volume according to EN 12897 [l]:	298
--	-----

---

$p_{\max}$ tank [bar]:	3
------------------------	---

---

$t_{\max}$ tank [°C]:	95
-----------------------	----

## Domestic hot water heat exchanger

---

Domestic hot water heat exchanger area [m <sup>2</sup> ]:	2,50
---	------

---

Domestic hot water heat exchanger volume [l]:	11
---	----

---

$p_{\max}$ Domestic hot water heat exchanger [bar]:	6
---	---

---

$t_{\max}$ Domestic hot water heat exchanger [°C]:	95
--	----

---

Zusatzwärmetauscher Fläche unten [m <sup>2</sup> ]:	1,70
---	------

---

Zusatzwärmetauscher Fläche oben [m <sup>2</sup> ]:	1,70
--	------

---

Zusatzwärmetauscher Volumen oben:	8
-----------------------------------	---

---

Zusatzwärmetauscher Volumen unten:	8
------------------------------------	---

## Zusatzwärmetauscher

---

$p_{\max}$ Zusatzwärmetauscher [bar]:	6
---------------------------------------	---

---

$t_{\max}$ Zusatzwärmetauscher [°C]:	95
--------------------------------------	----

## Connections

---

Connection layout:	Front / Back side
--------------------	-------------------

---

Connection sensor [Ø mm / terminal]:	6mm
--------------------------------------	-----

---

Connection cold / hot water:	R 1¼"
------------------------------	-------

---

Connection heat generator [thread]:	R 1"
-------------------------------------	------

---

Connection heating element [thread]:	Rp 1½"
--------------------------------------	--------