



CU-2235TBE
CU-2241TBE
CU-2250TBE



CU-3252TBE
CU-3268TBE
CU-4268TBE



CU-4280TBE
CU-5290TBE



Outdoor Unit Free Multi System Z • R32 GAS*

System Capacity (Min - Max Indoor Cooling Capacity Nominal)			3,2 to 5,7kW	3,2 to 6,0kW	3,2 to 7,7kW	4,5 to 9,5kW	4,5 to 11,2kW	4,5 to 11,5kW	4,5 to 13,6kW	4,5 to 17,5kW
Unit			CU-2235TBE	CU-2241TBE	CU-2250TBE	CU-3252TBE	CU-3268TBE	CU-4268TBE	CU-4280TBE	CU-5290TBE
Cooling capacity	Nominal (Min - Max)	kW	3,50 (1,50 - 4,50)	4,10 (1,50 - 5,20)	5,00 (1,50 - 5,40)	5,20 (1,90 - 7,20)	6,80 (1,90 - 8,00)	6,80 (1,90 - 8,80)	8,00 (3,00 - 9,20)	10,00 (2,90 - 11,50)
EER ¹⁾	Nominal (Min - Max)	W/W	4,86 (6,00 - 4,09) A	4,56 (6,00 - 3,80) A	4,24 (5,00 - 3,62) A	4,95 A	3,66 (7,04 - 3,38) A	4,39 (5,59 - 3,56) A	4,04 (5,66 - 3,21) A	3,5 (5,27 - 2,98) A
SEER	W/W	8,50 A+++	8,50 A+++	8,50 A+++	8,50 A+++	8,00 A++	8,00 A++	7,00 A++	6,50 A++	
Pdesign (cooling)		kW	3,5	4,1	5,0	5,2	6,8	6,8	8,0	10,0
Input power cooling	Nominal (Min - Max)	kW	0,72 (0,25 - 1,10)	0,90 (0,25 - 1,37)	1,18 (0,25 - 1,49)	1,09 (0,36 - 2,18)	1,86 (0,27 - 2,37)	1,55 (0,34 - 2,47)	1,98 (0,53 - 2,87)	2,86 (0,55 - 3,86)
Annual electricity consumption (cooling) ²⁾		kWh/a	144	169	206	214	298	298	—	—
Heating capacity	Nominal (Min - Max)	kW	4,20 (1,10 - 5,60)	4,60 (1,10 - 7,00)	5,60 (1,10 - 7,20)	6,80 (1,60 - 8,30)	8,50 (3,30 - 10,40)	8,50 (3,00 - 10,60)	9,40 (4,20 - 10,60)	12,00 (3,40 - 14,50)
Heating capacity at -7°C		kW	—	—	—	3,95	4,45	4,45	—	—
COP ¹⁾	Nominal (Min - Max)	W/W	4,88 (5,24 - 4,18) A	4,79 (5,24 - 3,91) A	4,63 (5,24 - 4,00) A	4,72 A	3,95 (5,32 - 3,64) A	4,47 (5,17 - 3,96) A	4,52 (6,00 - 3,46) A	4,20 (6,42 - 3,42) A
SCOP	W/W	4,60 A++	4,60 A++	4,60 A++	4,20 A+	4,20 A+	4,20 A+	4,00 A+	4,00 A+	
Pdesign at -10°C		kW	3,2	3,5	4,2	5,0	5,2	5,8	8,0	10,0
Input power heating	Nominal (Min - Max)	kW	0,86 (0,21 - 1,34)	0,96 (0,21 - 1,79)	1,21 (0,21 - 1,80)	1,47 (3,20 - 2,17)	2,15 (0,62 - 2,86)	1,90 (0,58 - 2,68)	2,08 (0,70 - 3,06)	2,86 (0,53 - 4,24)
Annual electricity consumption (heating) ²⁾		kWh/a	974	1,065	1,278	1,667	1,733	1,933	—	—
Current	Cooling / Heating	A	3,35 / 4,00	4,15 / 4,45	5,35 / 5,50	5,00 / 6,70	8,40 / 9,70	7,00 / 8,60	—	—
Power source		V	230	230	230	230	230	230	230	230
Recommended fuse		A	16	16	16	16	16	20	20	25
Recommended power cable section		mm ²	2,5	2,5	2,5	2,5	2,5	2,5	2,5	3,5
Sound pressure ³⁾	Cooling / Heating (Hi)	dB(A)	48 / 50	48 / 50	50 / 52	47 / 48	51 / 52	49 / 50	—	—
Dimensions ⁴⁾	H x W x D	mm	619 x 824 x 299	619 x 824 x 299	619 x 824 x 299	795 x 875 x 320	795 x 875 x 320	795 x 875 x 320	999 x 940 x 340	999 x 940 x 340
Net weight		kg	39	39	39	71	71	72	80	81
Piping connections	Liquid pipe	Inch (mm)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)
	Gas pipe	Inch (mm)	3/8 (9,52)	3/8 (9,52)	3/8 (9,52)	3/8 (9,52)	3/8 (9,52)	3/8 (9,52)	3/8 (9,52)	3/8 (9,52)
Elevation difference (in/out)	Max	m	10	10	10	15	15	15	15	15
Piping length total	Min - Max	m	3 - 30	3 - 30	3 - 30	3 - 50	3 - 60	3 - 60	—	—
Piping length to one unit	Min - Max	m	3 - 20	3 - 20	3 - 20	3 - 25	3 - 25	3 - 25	3 - 25	3 - 25
Pipe length for additional gas / Additional gas amount	m / g/m		20 / 15	20 / 15	20 / 15	30 / 20	30 / 20	30 / 20	—	—
Operating range	Cooling Min - Max	°C	-10 - +46	-10 - +46	-10 - +46	-10 - +46	-10 - +46	-10 - +46	-10 - +46	-10 - +46
	Heating Min - Max	°C	-15 - +24	-15 - +24	-15 - +24	-15 - +24	-15 - +24	-15 - +24	-15 - +24	-15 - +24

1) EER and COP classification is at 230V in accordance with EU directive 2002/31/EC. 2) The annual energy consumption is calculated in accordance with the ErP directive. 3) The Sound pressure of the units shows the value measured of a position 1m in front of the main body and 0,8m below the unit. The sound pressure is measured in accordance with Eurovent 6/C/006-97 specification. 4) Add 70 or 95mm for piping port.

Minimum quantity of connection: 2 indoor units. * Tentative data.